

DOP ULTL0501

- Unique identification code of the product-type:
Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Ultimate Laminate Flooring **Laminate floor coverings following EN13329 7-12 mm**
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Yayla BVBA, Smallandlaan 35 2660 Hoboken, Belgium
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
not applicable
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:
Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant):






Centexbel - NB 0493
Ghent University - NB 1611

not applicable

NOTIFIED BODY

CERTIFICATE OF CONSTANCY OF PERFORMANCE

- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not applicable
- Declared performance

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire		EN 14041:2004 / AC:2006
Content of Dangerous Substances		
Emission of HCHO		
Emission of VOC without HCHO	TVOC < 0,5 mg/m³	
Slip resistance		
Water-tightness	NA	
Electrical behavior (antistatic)		
Thermal conductivity [W/mK]	Th res (m2K/W) = 0,051 (7mm) Th res (m2K/W) = 0,055 (8mm) Th res (m2K/W) = 0,077 (10mm) Th res (m2K/W) = 0,071 (12mm)	

- The performance of the product identified in points 1 is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3
Signed for and on behalf of the manufacturer by:

Anil Cengiz Zaakuserde

(NAME AND FUNCTION)

Hoboken 24/04/2023

(PLACE AND DATE OF ISSUE)

YAYLA BV import export
SMALLANDLAAN 35
Hoboken 2660/BELGIUM
+32 3 2373481

info@yayla.be www.yayla.be

(SIGNATURE)

Clear form

Save